



[www.PetroRigs.com](http://www.PetroRigs.com)



[www.PetroRigs.com](http://www.PetroRigs.com)





# IMPORTANT

WHEEL BEARINGS AND  
WHEEL LUG NUTS MUST  
BE CHECKED AFTER FIRST  
50 MILES OF USE AND  
PERIODICALLY THEREAFTER

#1990017



## RIDEWELL SUSPENSIONS

### MONOPIVOT 240 BOLT TORQUE MINIMUM SPECIFICATIONS

ECCENTRIC PIVOT BOLT	1,000 FT. LBS. (1,350 N•m)
SHOCK BOLT	160 FT. LBS. (220 N•m)
AIR SPRING CONNECTION-3/4"	50 FT. LBS. (70 N•m)
AIR SPRING CONNECTION-1/2"	25 FT. LBS. (35 N•m)

After suspension has been in operation for approximately 6,000 miles (10,000 km), all fasteners must be re-tightened to specified torque. Repeat every 50,000 miles (80,000 km). DO NOT OVER TORQUE!

See Service Manual for Details

## TORQUE SPECIFICATIONS

**R**  
**S**

Covered Un

Ridewell Corporation





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)









[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)



WRITE ON THIS LABEL USE AN INDELIBLE, PERMANENT INK MARKER,  
PEN OR PENCIL THAT WILL NOT FADE IN DIRECT SUNLIGHT

ANNUAL VEHICLE INSPECTION LABEL NO.

EXPIRATION DATE: MONTH 6 YEAR 14  
RECORD OF THIS VEHICLE'S ANNUAL VEHICLE INSPECTION REPORT IS  
MAINTAINED AT: ☐ MOTOR CARRIER ☐ OTHER ENTITY  
HYDRO RESOURCES  
COMPANY / NAME  
4975 W WINNEMUKA BLVD  
STREET  
WINNEMUKA NEVADA 89445  
CITY, STATE, ZIP CODE  
725-5359 1181779  
TELEPHONE MOTOR CARRIER IDENTIFICATION NUMBER

NOTATION: THIS VEHICLE HAS PASSED AN INSPECTION IN ACCORDANCE  
WITH FMVSS 396.17 THROUGH 396.23.

IDENTIFICATION: IF THE VEHICLE IS NOT READILY, CLEARLY, AND  
PERMANENTLY MARKED, CHECK ONE AND COMPLETE.

UNIT NUMBER ☐ LICENSE / REGISTRATION NUMBER

IDENTIFICATION NUMBER ☐ OTHER  
4C9S30135DL266008

Printed by J.J. KELLER & ASSOCIATES, INC., Fresno, CA 93707-0368

43-SN (Rev. 5/95)



**INSPECTED**

THIS IS TO CERTIFY THIS  
STRUCTURE HAS BEEN  
INSPECTED AND IS SAFE  
TO OPERATE WITHIN THE  
CAPACITY LIMITATIONS AS  
SET BY THE ORIGINAL  
MANUFACTURER.

Inspected by:  
Woodrow Wilson, Jr. PE. OKLAHOMA 11176

Houston 77015 USA Woodward, OK 73801

Month ☐ 1 ☐ 2 ☐ 3 ☐ 4 ☒ 5 ☐ 6 ☐ 7 ☐ 8 ☐ 9 ☐ 10 ☐ 11 ☐ 12

Year 20 ☐ 11 ☐ 12 ☐ 13 ☐ 14 ☒ 15 ☐ 16 ☐ 17 ☐ 18 ☐ 19 ☐ 20





[www.PetroRigs.com](http://www.PetroRigs.com)



[www.PetroRigs.com](http://www.PetroRigs.com)







[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





www.PetroRigs.com



TO WRITE ON THIS LABEL USE AN INDELIBLE, PERMANENT INK MARKER, PEN OR PENCIL THAT WILL NOT FADE IN DIRECT SUNLIGHT

ANNUAL VEHICLE INSPECTION LABEL NO. 14802696

COMPLETED: MONTH 1 YEAR 19

A RECORD OF THIS VEHICLE'S ANNUAL VEHICLE INSPECTION REPORT IS MAINTAINED AT: ☐ MOTOR CARRIER ☐ OTHER ENTITY

HYDRO RESOURCES  
COMPANY/NAME

4975 W WINDMILL BLVD  
STREET

WINNEMUNGA ALABAMA 35445  
CITY, STATE, ZIP CODE

75 633-5759 1181779  
TELEPHONE MOTOR CARRIER IDENTIFICATION NUMBER

CERTIFICATION: THIS VEHICLE HAS PAID / FINES / STOP IN ACCORDANCE WITH 49CFR 396.17 THROUGH 396.23

VEHICLE IDENTIFICATION: IF THE VEHICLE IS NOT PERMANENTLY MARKED, CHECK ONE AND COMPLETE

☐ FLEET UNIT NUMBER ☐ LICENSE / REGISTRATION NUMBER

☐ VEHICLE IDENTIFICATION NUMBER ☐ OTHER

4C6N2621DA061576

© Copyright 1997 and Patented by A. J. HELLER & ASSOCIATES, INC., Tempe, AZ 85283-1008

**RIDEWELL SUSPENSIONS**

**MONOPIVOT 240 BOLT TORQUE MINIMUM SPECIFICATIONS**

ECENTRIC PIVOT BOLT	1,000 FT. LBS.	(1,350 N·m)
SHOCK BOLT	150 FT. LBS.	(200 N·m)
AIR SPRING CONNECTION 3/4"	70 FT. LBS.	(95 N·m)
4 R 5/16" 20 WRENCH 1/2"	140 FT. LBS.	(190 N·m)

See Service Manual for Details

**IMPORTANT**

WHEEL BEARINGS AND WHEEL LUG NUTS MUST BE CHECKED AFTER FIRST 50 MILES OF USE AND PERIODICALLY THEREAFTER

EQUIPPED WITH

**RIDEWELL SUSPENSIONS**



Covered Under U.S. and Foreign Patents, Existing and Applied For.  
www.ridewellcorp.com  
Ridewell Corporation P.O. Box 4556 Springfield, MD 21150-4556 (410) 833-4556

**TORQUE SPECIFICATIONS**

SPRING WHEELS - 100 FT. LBS. (135 N·m)

SHOCKS - 150 FT. LBS. (200 N·m)

STEERING KNUCKLE - 140 FT. LBS. (190 N·m)

WHEEL LUG NUTS - 70 FT. LBS. (95 N·m)



# NUTTALL TRAILERS

by C-All MFG., INC.

ATOKA, OKLAHOMA. USA

DATE OF MANUFACTURE DECEMBER 2002  
GVWR (UNIFORMLY DISTRIBUTED) 22,000 LBS. 9,979 KGS.  
GAWR ( MAXIMUM ALL AXLES) 55,000 LBS. 24,908 KGS.  
TIRES 235/75R22.5 VFY 850S 100D  
RIMS 2.25 X 22.5 STEEL UNIVERSAL  
COLD INFLATION PRESSURE 75 PSI 750 KPA  
THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S.A. FEDERAL  
MOTOR VEHICLE SAFETY STANDARDS IN EFFECT ON THE DATE OF  
MANUFACTURE SHOWN ABOVE.  
MODEL 2353C TYPE TRAILER  
VIN 1C9SCN232221000000

HYDRO RESOURCES



01096





A large yellow industrial engine, likely a Caterpillar model, is mounted on a metal platform. The engine is surrounded by various pipes, hoses, and electrical conduits. A large black fan is visible on the left side of the engine. The engine is connected to a large yellow pipe that runs across the platform. The background shows a clear blue sky and some structural elements of the platform. The text "www.PetroRigs.com" is overlaid in the center of the image.

[www.PetroRigs.com](http://www.PetroRigs.com)





**CAT**® SER. NO. JRE12638 ENGINE MODEL C15  
MODIFICATION NO. SEE ORDER MAX 1500 M  
AR NO. 254-3835 ALT 4922 FT  
CORE AR. ECM SOFTWARE 316-7381  
ECM NO. 1-21 ECU PART NO. 316-7381  
SERIAL NO. 540 HP 403.5 kW  
SERVICE TOOL TO VERIFY CURRENT ENGINE SETTINGS  
#3223530#11# 322-3538 Fuhda 115-5852

www.PetroRigs.com

FUEL



A low-angle, upward-looking photograph of an oil rig's pulley system. The image shows a large, yellow-painted metal structure with multiple horizontal pulleys. A thick black cable is visible, running through the pulleys. The background is a clear blue sky with the sun shining brightly in the upper right corner, creating a lens flare effect. The rig's structure is made of yellow metal beams and a diamond-patterned safety mesh. The overall scene is industrial and brightly lit.

[www.PetroRigs.com](http://www.PetroRigs.com)



CONTROLLER #1

OFF ON

**TWIN LIMIT**

**FORUM**

Automated Rig Brake Control System

"Smart" Crown Protection  
"Smart" Floor Protection  
Runaway Protection  
Precision Automatic Driller  
Brake Temp Safety Control  
Ton Mile Odometer  
Power Assist Brake Lever  
Power Parking Brake  
Remote Monitor & Record

PATENT RIGHTS RESERVED

Forum Oilfield Technologies LLC, Inc. 1180 Ponderosa Parkway, Houston, TX 77058  
Tel: 281-817-1070 Fax: 281-817-1070

[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)

**CW INDUSTRIES**  
Long Beach 562-432-5422  
Bakersfield 805-399-5422  
[www.cwindustries.us](http://www.cwindustries.us)



FRYDENSE, INC. DATE OF MFG. 09/17/11  
GIRARALL 25TH TIRE 4 RIMS 4  
9.0717KG (20.0 LB) 215/70R 22.5 (H) 22.5" 8"  
THIS VEHICLE STANDS PERMITS IN EFFECT ON THE DATE OF MFG.  
11/20/11 11/20/11 11/20/11 11/20/11

[www.PetroRigs.com](http://www.PetroRigs.com)

7 2 2 4





[www.PetroRigs.com](http://www.PetroRigs.com)



[www.PetroRigs.com](http://www.PetroRigs.com)







[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)



[www.PetroRigs.com](http://www.PetroRigs.com)

C.N.D. Lynn  
307-357-0710





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)



Woodrow Wilson, Jr. PE. OKLAHOMA 11176

Houston 77015 USA Woodward, OK 73801

Month (1) (2) (3) (4) (5) (6) (7) (8) (9) (10) (11) (12)

Year 20 (11) (12) (13) (14) (15) (16) (17) (18) (19) (20)

HYDRO RESOURCES

16-FT. SUBSTRUCTURE

[www.PetroRigs.com](http://www.PetroRigs.com)

This portable drilling structure is manufactured in compliance with the following specifications: AISC, AWS, and API specifications: 4E-4F-4G.

ROTARY CAPACITY-400,000 LBS.

SET-BACK 120,000 LBS.

MAXIMUM WIND 91-KTS.



TO WRITE ON THIS LABEL USE AN INDELIBLE, PERMANENT INK MARKER,  
PEN OR PENCIL THAT WILL NOT FADE IN DIRECT SUNLIGHT

ANNUAL VEHICLE INSPECTION LABEL NO.

COMPLETED: MONTH 6 YEAR 14

A RECORD OF THIS VEHICLE'S ANNUAL VEHICLE INSPECTION REPORT IS  
MAINTAINED AT: ☐ MOTOR CARRIER ☐ OTHER ENTITY

HYDRO RESOURCES

COMPANY / NAME

4975 W WINNEHUCKA BLVD

STREET

WINNEHUCKA NEVADA 89445

CITY, STATE, ZIP CODE

775 633-5111

TELEPHONE

4C9S30135 DL 266 008

MOTOR CARRIER IDENTIFICATION NUMBER

www.PetroRigs.com

CERTIFICATION: THIS VEHICLE HAS PASSED AN INSPECTION IN ACCORDANCE  
WITH 49CFR 396.17 THROUGH 396.23.

VEHICLE IDENTIFICATION: IF THE VEHICLE IS NOT READILY, CLEARLY, AND  
PERMANENTLY MARKED, CHECK ONE AND COMPLETE.

☐ FLEET UNIT NUMBER

☐ LICENSE / REGISTRATION NUMBER

☐ VEHICLE IDENTIFICATION NUMBER

☐ OTHER


4C9S30135 DL 266 008





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)