



www.PetroRigs.com



www.PetroRigs.com

CAUTION

GAUGE B

DERRICK ENGAGE HYDRAULIC PUMP
LEVER "B" UNTIL 300 P.S.I. IS
REACHED. RELEASE ANY AIR TRAPPED
IN CYLINDER BY CAREFULLY OPENING AIR
VALVE ON TOP OF RAISING CYLINDER.
TO REMOVE ALL AIR FROM
CYLINDER, RELEASE VALVE AND LOWER

PEMCO	
MODEL 104-220-0	SERIAL NO. 1000
HEIGHT 104 FT.	DATE 10-12-00
MAXIMUM RATED STATIC HOOK LOAD 220,000 LBS.	
CAUTION: ACCELERATION ON IMPACT LOADS, ALSO SET BACK AND WIND LOADS WILL REDUCE THE MAXIMUM RATED STATIC HOOK LOAD CAPACITY.	
MAXIMUM DISTANCE FROM DERRICK INDEX MARK TO WELL CENTERLINE 5 FT.	
MAXIMUM WIND RESISTANCE 65 MILES PER HR.	
ACTUAL VELOCITY: 10 MILES PER HR.	
API STD. 4	
SECOND EDITION	
WARNING: FAILURE TO FOLLOW INSTRUCTIONS ON CHECK CHART AND RECOMMENDED GUYING PATTERN PLATES MAY CAUSE RIG OVERTURN, MAJOR PROPERTY DAMAGE, PERSONAL INJURY AND DEATH.	
GONZA, TEXAS	

www.PetroRigs.com



www.PetroRigs.com



www.PetroRigs.com



www.PetroRigs.com



www.PetroRigs.com



www.PetroRigs.com



www.PetroRigs.com



www.PetroRigs.com