



[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





**CAUTION**  
CLASS 1, GROUP D  
TO PREVENT IGNITION OF HAZARDOUS  
ATMOSPHERES, THIS MOTOR SHOULD  
NOT BE PERMITTED IN AN AREA WHERE  
HAZARDOUS GASES, VAPORS, OR IGNITION  
TEMPERATURE 150°C (300°F) OR HIGHER  
MAY BE PRESENT.  
**ATTENTION**  
AFIN DE PREVENIR L'INFLAMMATION  
D'ATMOSPHERES DANGEREUSES, CE  
MOTEUR NE DOIT PAS ETRE PERMIS  
DANS UN ESPACE OU SE TROUVENT DES  
VAPEURS OU GAZ DONT LE POINT  
D'INFLAMMATION EST SUPERIEUR A 260°C.

**Corro-Duty**  
Inventable VT & 2:1

YCS0E2B AD76  
69 10-J/CS 6210-J/CS  
286Y FLC 935 001  
3 40 K09-AD76-M TE  
F CONT 1775  
30.0 230/460 1.15 60  
72.00/36.0 8.1 92.4  
EMERSON MOTOR COMPANY  
ST. LOUIS, MO

[www.PetroRigs.com](http://www.PetroRigs.com)



[www.PetroRigs.com](http://www.PetroRigs.com)







[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)





[www.PetroRigs.com](http://www.PetroRigs.com)



[www.PetroRigs.com](http://www.PetroRigs.com)







[www.PetroRigs.com](http://www.PetroRigs.com)

LOW ACCU. PRESS

LOW OIL LEVEL

LOW AIR PRESS

MOTOR RUN

MANIFOLD PRESSURE

ACCUMULATOR PRESSURE

ANNULAR PRESSURE

BYPASS  
LOW HIGH

ANNULAR  
OPEN CLOSE

ANNULAR  
DECREASE INCREASE

CHOKE  
OPEN CLOSE

UPPER PIPE RAM  
OPEN CLOSE

KILL  
OPEN CLOSE

SPARE  
OPEN CLOSE

BLIND RAM  
OPEN CLOSE

OPERATE

LOWER PIPE RAM  
OPEN CLOSE

ALARM  
ACKNOWLEDGE

LAMP  
TEST

XXX



[www.PetroRigs.com](http://www.PetroRigs.com)

