

[www.petrorigs.com](http://www.petrorigs.com)





[www.petrorigs.com](http://www.petrorigs.com)

[www.petrorigs.com](http://www.petrorigs.com)

**DANGER**  
CORR





[www.petro rigs.com](http://www.petro rigs.com)

[www.petrorigs.com](http://www.petrorigs.com)





[www.petrorigs.com](http://www.petrorigs.com)



[www.petrorigs.com](http://www.petrorigs.com)

[www.petrorigs.com](http://www.petrorigs.com)





[www.petrorigs.com](http://www.petrorigs.com)

A - PUMPS

PUMPS

**DANGER**  
THIS EQUIPMENT  
STARTS  
AUTOMATICALLY

**WARNING**  
Compressed Air  
WARNING  
Compressed Air

25D4

Sullivan  
Palatek

**Air**  
Specialty  
EQUIPMENT COMPANY  
CORPUS CHRISTI, TEXAS 78401  
800-886-6700  
361-661-7900

[www.petrorigs.com](http://www.petrorigs.com)

Sullivan  
Palatek

**DANGER**  
COMPRESSED  
AIR



[www.petrorigs.com](http://www.petrorigs.com)

AUTHORIZED  
PERSONNEL  
ONLY

[www.petrorigs.com](http://www.petrorigs.com)



A photograph of industrial machinery, including a large green motor and various pipes and valves, mounted on a rusty metal pallet. The equipment is situated outdoors, possibly in a storage yard or workshop. A blue plastic container is visible on the left side of the pallet. The background shows more industrial structures and a clear sky.

[www.petrorigs.com](http://www.petrorigs.com)

# MAGNA

DVR



## SYNCHRONOUS AC GENERATOR

MODEL	[REDACTED]	
SERIAL	[REDACTED]	
FRAME	[REDACTED]	TYPE [REDACTED]
PH	[REDACTED]	[REDACTED]
ENCL.	[REDACTED]	[REDACTED] °C
INS. CLASS	[REDACTED]	RISE BY INS. [REDACTED] °C
FIELD WINDS	[REDACTED]	FIELD VOLTS [REDACTED]
	CONTINUOUS	
KVA	[REDACTED]	VOLTS [REDACTED]
	[REDACTED]	AMPS [REDACTED]
KW	[REDACTED]	VOLTS [REDACTED]
	[REDACTED]	AMPS [REDACTED]
BEARING	[REDACTED]	BEARING [REDACTED]
REGULATOR NO.	[REDACTED]	[REDACTED]

[www.petrorigs.com](http://www.petrorigs.com)

**LUBRICATING INSTRUCTIONS**  
LUBRICATE GENERATOR EVERY [REDACTED] HOURS OR ANNUALLY WITH [REDACTED] CHEVRON SRI OR EQUIVALENT GREASE WITH A TEMPERATURE RANGE OF 30°C TO 175°C

**MARATHON**  
**ELECTRIC**  
WALWORTH, WISCONSIN 54980 U.S.A.

[www.petrorigs.com](http://www.petrorigs.com)





[www.petrorigs.com](http://www.petrorigs.com)





[www.petrorigs.com](http://www.petrorigs.com)

A large, rusted industrial pipe structure, possibly a wellhead or separator, is mounted on a flatbed trailer. The structure is made of heavy metal and shows significant signs of wear and corrosion. It features a large, curved pipe at the top and a series of vertical supports. The trailer is parked on a gravel surface, and the background consists of green trees and a clear blue sky. A watermark 'www.petrorigs.com' is overlaid in the center of the image.

[www.petrorigs.com](http://www.petrorigs.com)



[www.petrorigs.com](http://www.petrorigs.com)

A large green industrial pump unit is the central focus, featuring two prominent green electric motors on a wooden base. Above the unit is a yellow metal walkway with railings. The unit is situated on a gravel surface next to a green metal structure. In the background, there are green bushes and a clear blue sky. A large black hose lies on the ground in the foreground. The website address 'www.petrorigs.com' is overlaid in white text across the middle of the image.

[www.petrorigs.com](http://www.petrorigs.com)



[www.petrorigs.com](http://www.petrorigs.com)

[www.petrorigs.com](http://www.petrorigs.com)



[www.petrorigs.com](http://www.petrorigs.com)

The image shows a large, blue-painted industrial metal frame, likely for a wellhead or similar equipment. The structure consists of several horizontal and vertical beams, with a central vertical beam that has a Y-shaped cross-section. The metal shows signs of wear and rust. A watermark is overlaid on the center of the image.

[www.petrorigs.com](http://www.petrorigs.com)





[www.petrorigs.com](http://www.petrorigs.com)



[www.petrorigs.com](http://www.petrorigs.com)



[www.petrorigs.com](http://www.petrorigs.com)

The image shows a complex, heavily rusted metal structure, likely part of an oil or gas rig. The metal is dark brown and orange with significant yellowish-orange rust patches. The structure consists of various beams, pipes, and flanges. In the foreground, there are several large, cylindrical metal components, some with circular openings. A white flange with four bolt holes is visible in the middle ground. The background is slightly out of focus, showing more of the structure and a glimpse of a concrete or metal surface. The overall scene is industrial and aged.

[www.petrorigs.com](http://www.petrorigs.com)

[www.petrorigs.com](http://www.petrorigs.com)





Weatherford International Ltd.  
515 Post Oak Blvd., Suite 600  
Houston, Texas 77027 USA

### Model MP-8

		PISTON SIZE	RATED PSI
PISTON NUMBER	4.00"	4.00"	6,000
SEAL NUMBER	4.50"	4.50"	4,200
RATED POWER	800 HP	5.00"	3,575
STROKE LENGTH	9 INCH	5.50"	2,950
INTERNAL GEAR RATIO	4:185:1	6.00"	2,475
MAXIMUM CRANK SPEED	150 RPM	6.50"	2,100
OIL CAPACITY	65 GAL		

Made in China

[www.petrorigs.com](http://www.petrorigs.com)



[www.petrorigs.com](http://www.petrorigs.com)



宝鸡石油机械有限公司  
BAOJI OILFIELD MACHINERY CO., LTD.  
中国宝鸡 BAOJI, CHINA

[www.petrorigs.com](http://www.petrorigs.com)

功率: 59.6kW  
MAX HP: 80  
缸套直径, in: 6 3/4  
LINER SIZE: 168  
压力, MPa: 13.5  
PRESSURE, PSI: 1955

润滑油  
壳牌下面推荐的合功油  
型板正油...  
环境温度...  
油温...  
油压...





[www.petrorigs.com](http://www.petrorigs.com)



# 宝鸡石油机械有限责任公司

BAOJI OILFIELD MACHINERY CO., LTD.

中国 宝鸡 BAOJI, CHINA

[www.petrorigs.com](http://www.petrorigs.com)

型号: F-800 钻井泵 排量: 150l/min 出厂号: 405-2000 日期: 04-12  
TYPE: MUD PUMP PUMP SPEED SERIAL DATE

功率: 596kW 齿轮速比: 4.185:1 整机重量: 14.5t 长×宽×高: 3983×3324×235mm  
MAX.HP GEAR RATIO WEIGHT LXWXH

缸套直径, in:	6 3/4	6 1/2	6 1/4	6	5 1/2	5
LINES SIZE						
压力, MPa:	13.5	14.6	15.8	17.1	20.4	24.7
PRESSURE, PSI:	1955	2115	2290	2480	2960	3580

## 润滑规范

使用下面推荐的含防锈、防腐蚀、抗泡沫和硫磺  
型抗磨损添加剂的齿轮油:

环境温度+10°C至+66°C L-CKD 460或API GL-5, SAE 85W-140  
环境温度-7°C至+38°C L-CKD 320或API GL-5, SAE 85W-90  
环境温度-29°C至+18°C API GL-5, SAE 80W-90

油缸容量: 246L CAPACITY: 65 US GAL.

## LUBRICATION SPEC.

USE ANTI-CORROSIVE, ANTI-RUSTING,  
ANTI-FOAMING, S&P TYPE EXTREME PRESSURE,  
ANTIFRAYING ADDITIVE GEAR LUBRICANT.

TEMP. +10°C TO +66°C AGMA WLD EP 67  
TEMP. -7°C TO +38°C AGMA WLD EP 66  
TEMP. -29°C TO +18°C AGMA WLD EP 62



宝鸡石油机械有限责任公司

BAOJI OILFIELD MACHINERY CO., LTD.

中国宝鸡 BAOJI CHINA

www.petrorigs.com

型号: F-800	钻井泵	冲数: 150r/min	出厂编号: A05-2000	出厂日期: 04-12
TYPE: F-800	MUD PUMP	PUMP SPEED	SERIAL	DATE
功率: 596kW	齿轮速比: 4.185:1	整机重量: 14.5t	长×宽×高: 3988×3324×2331mm	
MAX.HP	GEAR RATIO	WEIGHT	LXWXH	
缸套直径, in:	6 3/4	6 1/2	6 1/4	6
LINER SIZE				5 1/2
压力, MPa:	13.5	14.6	15.8	17.1
PRESSURE, PSI:	1955	2115	2290	2480
				2660
				2850

润滑规范

使用下面推荐的含防锈、防腐蚀、抗泡沫和硫磷  
压抗磨损添加剂的齿轮油:

环境温度+10°C至+88°C L-CKD 460或API GL-5, SAE 85W-140  
 环境温度-7°C至+38°C L-CKD 320或API GL-5, SAE 85W-90  
 环境温度-29°C至+18°C API GL-5, SAE 80W-90  
 油液容量: 246L CAPACITY: 65 US GAL.

LUBRICATION SPEC.

USE ANTI-CORROSIVE, ANTI-RUSTING,  
 ANTI-FOAMING, S&P TYPE EXTREME PRESSURE,  
 ANTI-FRAYING ADDITIVE GEAR LUBRICANT.  
 TEMP. +10°C TO +88°C AGMA MIL-EP-67  
 TEMP. -7°C TO +38°C AGMA MIL-EP-68  
 TEMP. -29°C TO +18°C AGMA MIL-EP-62

[www.petrorigs.com](http://www.petrorigs.com)

HAZARDOUS  
MATERIAL  
STORAGE  
**DANGER**  
NO SMOKING  
FLAMMABLE

**NOTICE**  
NO SMOKING  
NO EATING  
NO DRINKING  
BEYOND THIS POINT





[www.petrorigs.com](http://www.petrorigs.com)



[www.petrorigs.com](http://www.petrorigs.com)



[www.petrorigs.com](http://www.petrorigs.com)