



**DANGER**  
**HIGH VOLTAGE**

NAMEPLATE  
SPECIFICATIONS  
SERIAL NO. 123456  
MFG. DATE 10/2010

[www.PetroRigs.com](http://www.PetroRigs.com)



BRANDON & CLARK INC.

[www.PetroRigs.com](http://www.PetroRigs.com)

B&C ID NUMBER

284377 2-28-08

## BEARING LUBRICATION

REPLENISH GREASE IN BEARINGS USING APPROXIMATELY THE AMOUNTS OF GREASE LISTED BELOW AND AT INTERVALS SHOWN IN RUNNING TIME HOURS OR MONTHS, WHICHEVER OCCURS FIRST. DO NOT OVERFILL. STOP FILLING WHEN GREASE BEGINS TO DRAIN FROM RELIEF VALVE OR FROM AROUND SHAFT. WIPE EXCESS GREASE FROM INTERNAL PARTS OF UNIT.

USE A HIGH QUALITY NGL 1 GRADE 2 ELECTRIC MOTOR BEARING GREASE WHICH WILL LUBRICATE SATISFACTORILY OVER A RANGE FROM LOWEST AMBIENT TEMPERATURE EXPECTED TO + 250°F.

OUTBOARD OR DRIVE END  
EXHAUST

[www.PetroRigs.com](http://www.PetroRigs.com)

### BEARING NUMBER

012-21202-00

012-42240-05

### REPLENISH INTERVAL IN RUNNING TIME HOURS

4800

5500

### REPLENISH INTERVAL IN MONTHS

12

### REPLENISH AMOUNT IN OUNCES

2.7

8

**KATO ENGINEERING**

RELIANCE ELECTRIC





[www.PetroRigs.com](http://www.PetroRigs.com)



[www.PetroRigs.com](http://www.PetroRigs.com)



[www.PetroRigs.com](http://www.PetroRigs.com)

[www.PetroRigs.com](http://www.PetroRigs.com)

**HIGH VOLTAGE**

**NOTICE**  
AUTHORIZED  
PERSONNEL ONLY

**CAUTION**  
DO NOT WASH  
DOWN WITH  
WATER HOSE

