



[www.PetroRigs.com](http://www.PetroRigs.com)

[www.PetroRigs.com](http://www.PetroRigs.com)

**DANGER**  
HIGH  
VOLTAGE  
GAS  
HEAT  
PRESSURE

LOCK-OUT / TAG-OUT  
ALL ENERGY SOURCES  
BEFORE REMOVING  
GUARDS

**DANGER**





[www.PetroRigs.com](http://www.PetroRigs.com)



[www.PetroRigs.com](http://www.PetroRigs.com)

HIGH  
VOLTAGE

**NOTICE**

AUTHORIZED  
PERSONNEL ONLY

DO NOT  
WATER



[www.PetroRigs.com](http://www.PetroRigs.com)

WARRANTY INFORMATION  
KATO ENGINEERING

WARRANTY INFORMATION  
KATO ENGINEERING

REPLACE OIL FILTER	REPLACE OIL FILTER
REPLACE OIL FILTER	REPLACE OIL FILTER
REPLACE OIL FILTER	REPLACE OIL FILTER
REPLACE OIL FILTER	REPLACE OIL FILTER
REPLACE OIL FILTER	REPLACE OIL FILTER

KATO ENGINEERING

ELECTROQUIP  
ELECTROQUIP

EVANS ELECTROQUIP  
EVANS ELECTROQUIP

EVANS ELECTROQUIP  
EVANS ELECTROQUIP

**KATO ENGINEERING**  
*RELIANCE ELECTRIC*



Mankato, Minnesota USA.

[www.PetroRigs.com](http://www.PetroRigs.com)





# SYNCHRONOUS AC GENERATOR

SERIAL NUMBER: 64894-1  
CATALOG: 6P6-3150  
MODEL NUMBER: 1050-685361121  
TYPE NUMBER: 20971

IMPORTANT: WHEN ORDERING PARTS INCLUDE SERIAL AND TYPE NUMBERS.

## ALTERNATOR

KW CONT.	KW STANDBY	PHASE	HZ
1050		3	60
KVA CONT.	KVA STANDBY	P.F.	RPM
1500		.7	1200

FIELD VOLTS
347/600

AMPERES	GEN. FLD. AMPS
1445	

TEMP. RISE	DESIGN AMB.	INSUL. CLASS	WIRE
80R °C	40 °C	F	6

## EXCITER

EXC. ARM. "C" NUMBER: 12058-42  
EXC. FLD. "C" NUMBER: 12090-42

FIELD AMPS	EXC. FLD. VOLTS
5.0	50

MANKATO, MINNESOTA U.S.A.

KATO ENGINEERING  
RELIANCE ELECTRIC



www.PetroRigs.com

157-00103-00



# GULF ELECTROQUIP

S/N 54826-84894

DATE 4/08

HP.

KW

F.L. RPM

VOLTS

P.F./S.F.

MAKE

AMPS

CYCLES

PHASE

TYPE

FRAME

°C RISE

SEC. V.

SEC. A.

EXC. V.

BEARING#

P.E. 22224

O.P.E. 22320

RECON.

EMERGENCY REPLACEMENT SERVICE & PARTS  
(713) 675-2525

[www.PetroRigs.com](http://www.PetroRigs.com)



# BEARING LUBRICATION

REPLENISH GREASE IN BEARINGS USING APPROXIMATELY THE AMOUNTS OF GREASE LISTED BELOW AND AT INTERVALS SHOWN IN RUNNING TIME HOURS OR MONTHS, WHICHEVER OCCURS FIRST. STOP FILLING WHEN GREASE BEGINS TO DRAIN FROM RELIEF VALVE OR FROM AROUND SHAFT.

USE DI-ESTER OIL-LITHIUM SOAP GREASE WHICH WILL LUBRICATE SATISFACTORILY TO A TEMPERATURE OF PLUS 250°F.

GREASE CONFORMING TO SPECIFICATION MIL-G-23827A IS RECOMMENDED.

BEARING NUMBER

BEARING NUMBER

DRIVE END [www.PetroRigs.com](http://www.PetroRigs.com) NON END

012-02240-06

012-22200-00

REPLENISH INTERVAL IN RUNNING TIME HOURS

5500

4800

REPLENISH INTERVAL IN MONTHS

12

12

REPLENISH AMOUNT IN OUNCES

.8

1.4

**KATO** Engineering  
SUBSIDIARY OF RELIANCE

P-157-00054-01



**EVANS ENTERPRISES, INC.**

SINCE 1954  
[www.goevans.com](http://www.goevans.com)

BRG. BRAND & SIZE	SHAFT	OPP
NAOHI	22224	22320
REPAIR ORD#	MECHANIC	DATE
21442	MU KT	01/15

[www.PetroRigs.com](http://www.PetroRigs.com)



OKC • TULSA • PRYOR  
ROGERS • FT. SMITH • CONWAY  
SPRINGFIELD • WICHITA FALLS • WACO

REBUILT USING PREMIUM C3 FIT  
ELECTRIC MOTOR QUALITY BEARINGS  
RELUBE WITH MOBIL POLYREX  
EM GREASE ONLY