

**Atlas Copco Predator Rig, Low Hour Rig**

SPECS:

C-27 Caterpillar Deck Engine, Rated 950hp

Fuller RTO F-14908LL 8-Speed Transmission

500hp Hydraulic Drive Motor, 69,000lb Tridem

Rear Axles w/ Driver Controlled Inter-Axle w/ Differential Locks, 44,000lb Tandem Front Axles

445/65R22.5 Tubeless Radial Steer Tires w/ 11R22.5 / 14 Ply Tubeless Radial Rear Tires

ABS Braking w/ Low Profile Two Man Cab

150 Gallon Aluminum Fuel Tank

Range III Hydraulically Telescoping Tower, Rated 200,000lb Maximum Hook Load

Hydraulically Actuated, Two Speed, Tilt Out, Top Head Drive Assembly, Rated 30,000lbs Torque

5" ID Spindle

Predator Sub Structure Support System

42" Floor Opening, 27 ½" Table Opening, 17 ½" Slip Bushing

Hydraulic Slips & Roughneck

10' x 24' x 8' Work Floor

4.2 Ton Electric Floor Crane

3,000psi Air/Mud Piping

Oilfield Night Lighting Package

Offboard Generator Connection

Self-Contained Drillers Console w/ Military Grade Flat Screen Monitor

Easy Access Hydraulic Valve Bank

Catwalks, Railings, Fold Up Rig Floor Deck

Predator Hands Free Tubular Loading System

4 ½" to 24" Diameter Capability from 30' to 42' Lengths

9,000lb Maximum Handling Weight Capacity

Remote Loading & Driller Console Connection Operating Controls

Self-Contained Oilfield Skid Mounted

Alco Table Slips & Holders Dressed to 4 ½"



Skate Clamps up to 13 3/8"

Located in the Permian Basin Area

