

(2) 'Nice Used, Low Hour' Bowen S 3.5 120 Ton Power Swivel p/b 9.0L John Deere Diesel Power Unit Skid Mounted with Air Control Panel and 100' Foot Hose Reel. Unit will be tested and come packaged complete with certification papers.

Unitized 3.5 Power Swivel System, with:

- Swivel Head

- * Max Torque: 8100 ft-lbs
- * Max Speed: 150 rpm
- * Nominal Load Rating: 120 tons
- * 100 RPM Load Rating: 65 tons
- * Standard saver sub connection: 3"-8 Line Pipe Thread
- * Goose Neck Access Hole Diameter: 2-1/2" NPT
- * Max Circulating Pressure: 5000 PSI
- * Bore thru Stem: 2-1/4" oElevator Bail: 3-1/2" and 4-1/2"
- * Gear Oil Capacity: 4-1/2 gallons
- * High Pressure Hose Size: 1-1/4"
- * Drain Hose Size: 1"

- Engine: John Deere 9.0L 6090-HF485 with electric start

- * Engine control system mounted on a shock isolated panel consisting of tachometer, hour meter, push button, start switch, volt meter, oil pressure gauge, water temp gauge
- * Safety shutdown system for low oil pressure, high water temperature

- Fuel Tank: 100 gallons

- Hydraulic Reservoir: 75 gallons

- 12v battery and battery box, and utility/tool box

- Pneumatic controls with torsion control valve

- Hydraulically driven hose reels with 100 feet of hydraulic hose

- Remote control panel with 50 feet of hose

- Skid mounted or Tandem Axle Gooseneck Trailer

SPECIFICATIONS

WEIGHT	2,000 LBS
MAX TORQUE	8,100 FT-LBS
MAX SPEED	150 RPM
NOMINAL LOAD RATING	120 TONS
100 RPM LOAD RATING	65 TONS
MAX CIRCULATING PSI	10,000 PSI
TELESCOPED	44-1/8"
EXTENDED	64-1/8"
GOOSE NECK CONNECTION	3" - 8, LINE PIPE THREAD
SAVER SUB CONNECTION	3-1/2" API IF
GOOSE NECK ACCESS HOLE	2-1/2" NPT
SAVER SUB MAKE-UP TORQUE	7,500/10,000 FT-LBS