


1500HP - SCR, 7500PSI, Walking Capable



HOISTING, ROTATING & PIPE-HANDLING EQUIPMENT

Drawworks: Oilwell 840E

Rotary Table: 27.5"

Traveling Block: 500 Ton

Top Drive: TDS- 11SA

Iron Roughneck: Forum FH-80

Hydraulic Catwalk: Hydraulic NOV

Static Hook Load: 750,000#

MAST & SUBSTRUCTURE

Mast Design: Pyramid Derrick & Equipment Corp.

Mast Height: 142'

Racking Capacity: 23,000' of 5" Drill Pipe

Floor Height: 26'-6" / Rotary Beam Clearance: 22'

TRANSPORT

Estimated Loads: 60
without drill pipe

POWER PACKAGE

Engines: Three (3) Caterpillar 3512C Diesel

Engines Dual Gas: N/A

Generators: Three (3) 1365 Kw Kato

SCR System : Ross Hill Electric- Model 1400


MUD SYSTEM

Mud Pumps: Three (3) F1600 with 7500 psi Fluid Ends

Liquid Mud Tanks: Two (2) w/ 1100 bbl Total Capacity

Trip Tank: 80 bbl Total Capacity

Shale Shakers: One (1) Dual Hyperpool



BOP EQUIPMENT

Annular: 13-5/8" 5K

Single Ram: 13-5/8" 10K

Double Ram: 13-5/8" 10K

Accumulator: B.O.P.C. Inc.

Choke Manifold: 10K

Mud/Gas Separator: Shop Built

TUBULARS

Drill Pipe: 5" Drill Pipe as Needed

Drill Collars: As needed per Customer's Well Program

PAD DRILLING (MULTI DIRECTIONAL)

Walking System/Type: Veristic Mfg. (Stomper Type)

Pad Walking Distance : 0'-100'