## 2010 Service King SK-675 Specs

Service King 665HP Carrier Mounted Drilling Rig, 6-Axle Carrier Rig Rated at 10,000' Drilling Depth

<u>Carrier:</u> 2010 Service King Model Sk-675, 6-Axle Carrier, 665HP Detroit, 4500 OFS Allison Transmission

<u>Drawworks:</u> 2010 Service King Model 42 x 12 Water Cooled Drums with Hercules Quick Release Deadline Anchor S/N DW 2121

<u>Mast:</u> Service King 109 ft Telescoping w/Static Hook Load of 315,000-LB, Racking Board with Crown Saver, S/N DK303 Upper dog house

Substructure: 8 ft x 13 ft Cantilever with Base Beam, 350,000-LB Setback Capacity

Brake: Double Disc Assist 48 inch x 8 inch

Rotary Table: Wheland 20-1/2 inch Rotary Table

Blocks: 150-Ton Sentry, 4-Sheave, 8-Lines with Spring Hooks

## Miscellaneous:

Kelly With Roller Bushings: 40 ft 5-1/4 Hex Kelly Spinner: N.O.V. Hydraulic Forward And Reserve Automatic Driller: Schwab's Pilot II Automatic Driller Straight hole tool-incomplete Elevators: DP 4-1/2 inch 150-Ton BN Casing 7 inch 5-1/2 inch 4-1/2 inch 9-5/8 inch Portable Steel Building w/Water Tank 200 BBL Capacity, Tool Shed, Cathead: Hydraulic Drilling Rig Pad Approximately 35 ft x 16 ft x 4 inch Square Tube Construction; Ramp Approximately 36 ft TIW Valve; Complete Winterization Package w/Tarps