

www.PetroRigs.com





www.PetroRigs.com



The image shows a close-up, low-angle view of an offshore oil rig platform. The structure is composed of a complex network of white-painted steel beams and cross-braces. Several yellow-painted vertical support poles are visible. In the foreground, there are large green cylindrical components, likely part of a hoist or winch system. One of these green cylinders has a circular logo with the letters 'RMT' inside. Thick, dark steel cables are draped across the structure, secured with heavy-duty metal chains. The background shows a cloudy sky. A watermark is overlaid on the center of the image.

www.PetroRigs.com



www.PetroRigs.com



www.PetroRigs.com



www.PetroRigs.com



www.PetroRigs.com

www.PetroRigs.com



www.PetroRigs.com

seats



www.PetroRigs.com



www.PetroRigs.com

MODEL NO. 96-2P-215M
SERIAL NO. TD-142
DATE OF MANUFACTURE 10-21-82
HEIGHT 96 FEET
MAXIMUM STATIC HOOK LOAD V. JAW LINES
215,000 POUNDS ON 6 LINES
180,000 POUNDS ON 4 LINES
MAXIMUM WIND CAPACITY 70 M.P.H.
80 3/8 CROSSOVER
ANGLE OF LEAN 3 3/4

CAUTION
ACCELERATION OR IMPACT, ALSO
SETBACK AND WIND LOADS, AND
INCREASED PELL SPACING WILL
REDUCE PERFORMANCE RATED
HOOK LOAD CAPACITY.

NOTE
AT THE OPERATOR'S DISCRETION
THIS MAST MAY BE USED WITH
GUYS AND ANCHORS WHICH
CONFORM TO THE RECOMMENDATIONS
FOR GENERAL CONDITIONS CONTAINED
IN A.P.I. STANDARD 4E.

GUYS	BREAKING STRENGTH
(A)	35 800
(B)	35 800
(C)	35 800
(D)	23 000
(E)	23 000



RIG EQUIP MANUFACTURING INC.
VICTORIA, TEXAS

www.PetroRigs.com





www.PetroRigs.com

A close-up photograph of industrial machinery, likely part of an oil rig. The central focus is a large, red-painted metal flange or coupling, which shows significant rust and wear. It is bolted to a green structural beam. To the right, another green beam runs diagonally across the frame. In the background, a metal safety cage with a diamond mesh is visible. Various black hoses and smaller metal components are also present. The overall scene is outdoors, with green foliage visible through the cage.

www.PetroRigs.com



www.PetroRigs.com



www.PetroRigs.com



www.PetroRigs.com

www.PetroRigs.com





www.PetroRigs.com



www.PetroRigs.com



www.PetroRigs.com



www.PetroRigs.com



www.PetroRigs.com



www.PetroRigs.com

YED
SEL
Y



www.PetroRigs.com



www.PetroRigs.com



DATE OF MANUFACTURE 2014-11 SERIAL NUMBER RS14-037  API 7K-0095

RONGSHENG MACHINERY MANUFACTURE LTD. OF HUABEI OIL FIELD

www.PetroRigs.com

PERFORMANCE	AT	MAXIMUM	440HP	INPUT	& 220SPM
DIAMETER OF LINER (in)	4 1/2	4 1/2	4	3 3/4	3 1/2
RATED OUTPUT PRESSURE (psi)	2451	2740	3130	3523	4045
GALLONS PER REVOLUTION	1.239	1.105	0.979	0.861	0.750
GEAR RATIO	4.528:1				
STROKE LENGTH	6"				
VALVE SIZE	HP#4				
CRANKCASE OIL CAPACITY	35GAL				
PUMPS DIMENSIONS	8 1/2" x 4" x 4 1/2"				
WEIGHT COMPLETE LESS SHEAVE	9842 lb				



www.PetroRigs.com

www.PetroRigs.com



www.PetroRigs.com