

No	Description	Qty
1	<p>131092 14" HYDRA-SHIFT CASING TONG MODEL C, WITH LIFT CONTROL, WEDGE DRIVE TRI-GRIP BACKUP, SERIES DOOR INTERLOCK, MOTOR PORT RELIEF VALVE, RADIAL LOCK DOOR, HI-LOW MOTOR SPEED SELECTOR VALVE, CASE HANDLES (2) AND SOLID HANGER</p> <p>HS Code: 8430.49.8010</p> <p>Capacity (Pipe O.D.):</p> <p>Tong 4 - 14 in. (101.6 - 355.6 mm)</p> <p>Backup ... 4 - 15 in. (101.6 - 381.0 mm)</p> <p>Size 45 x 63.5 in. (1143 x 1612.9 mm)</p> <p>Weight 4,000 lbs. (1814.4 kg)*</p> <p>Maximum Torque @ 2500 psi (172 bar)</p> <p>High-high 5,500 ft-lbs (7457 Nm)</p> <p>High-low 11,000 ft-lb (14914 Nm)</p> <p>Low-high 17,500 ft-lb (23727 Nm)</p> <p>Low-low 35,000 ft-lb (47454 Nm)</p> <p>Gear Ratio</p> <p>High 26.29:1</p> <p>Low 95.23:1</p> <p>Maximum RPM @ 65 GPM (246 LPM)</p> <p>High-high 80 RPM</p> <p>High-low 42 RPM</p> <p>Low-high 22 RPM</p> <p>Low-low 11 RPM</p> <p>Handle Length 36.5 in. (927.1 mm)</p> <p>Tong Requires (2) "GG" Series Heads Backup Requires (3) "GGW" Series Heads</p>	2
2	<p>USAGE KIT, TONGS WITH TONGS WITH PIVOT HEADS AND TRI-GRIP BACKUPS</p> <p>HS Code: 8430.49.8010</p>	2
3	<p>LIFT CYLINDER ASSEMBLY, 4" BORE X 48" STROKE</p> <p>HS Code: 8431.39.0050</p>	2
4	<p>SPRING HANGER ASSEMBLY, TRIPLE (4,000 - 6,000 LB CAPACITY)</p> <p>HS Code: 8430.49.8010</p>	2
5	<p>TORQUE GAUGE ASSEMBLY, COMPRESSION TYPE 0-40,000 FT-LBS, US/METRIC SCALE, 36.5" HANDLE, 14" HS WITH BACKUP</p> <p>HS Code: 9031.80.8080</p> <p>Torque Gauge Assembly Comes Complete With:</p> <p>1) 6" Diameter Guage Assembly Including:</p> <ul style="list-style-type: none"> - 0-40,000 ft-lbs Full Range Dial - Dual Scale: US (ft.-lbs.) / Metric (Nm) <p>5) - Includes Low Pressure Damper</p> <ul style="list-style-type: none"> - Includes Target Pointer - Calibrated for 36.5" Torque Handle Length <p>2) 12.0 sq. inch Compression Type Load Cell</p> <p>3) 6 Ft Connecting Hose With Fittings</p> <p>4) Hand Pump for Load Cell Fluid</p> <p>5) (1) Pint Load Cell Fluid</p>	2
	<p>HEADS FOR RIG DIES FOR USE ON CARBON STEEL API TUBULARS FOR THE TONG:</p> <p>QTY OF (2) IS REQUIRED TO COMPLETE SET</p>	
7	<p>HEAD, PIVOT, GG-5-1/2", 4.00 EA FOR RIG DIES</p> <p>HS Code: 8430.49.8010</p>	4
8	<p>HEAD, PIVOT, GG-7", FOR RIG DIES</p> <p>HS Code: 8430.49.8010</p>	4
9	<p>HEAD, PIVOT,GG-9-5/8", FOR RIG DIES</p> <p>HS Code: 8430.49.8010</p>	4
10	<p>HEAD, PIVOT,GG-13-3/8" FOR RIG DIES</p> <p>HS Code: 8430.49.8010</p>	4
	<p>HEADS FOR RIG DIES FOR USE ON CARBON STEEL API TUBULARS FOR THE BACKUP:</p> <p>QTY OF (3) IS REQUIRED TO COMPLETE A SET</p>	
11	<p>HEAD, BACKUP, GGW-5-1/2", FOR RIG DIES</p>	6
12	<p>HEAD, BACKUP, GGW-7", FOR RIG DIES</p>	6
13	<p>HEAD, BACKUP, G GGW-9-5/8", FOR RIG DIES</p>	6
14	<p>HEAD, BACKUP, GGGW-13-3/8", FOR RIG DIES</p>	6
	<p>DIES IN ALL HEADS FOR TONG AND BACKUP.</p>	
15	<p>DIE, RIG, 1/2" THICK X 1-1/4" WIDE X 3-7/8" LONG SPARE PORT RELIEF VALVES FOR TONGS</p>	64
16	<p>VALVE, PORT RELIEF 391-1873-006 HI-BOY VALVE COMMERCIAL DV-PRV-AC For DVA20 & 35 Valves</p>	2