

Cabot 550HP Drilling Rig Specs/Inventory

Cabot 550HP double drum, back-in drilling unit, lebus grooved f/ 1 1/8" line p/b Detroit series 60 diesel engine, Allison 5861-4 transmission, 15" dbl hydromatic brake, tu-flo air compressor, Quincy 325 air compressor, Cabot/franks 108'h, 269,000# statue hook load, telescoping mast, hydraulically raised, 4-sheave crown block, crown safety platform, ladder & guylines, Wilson 200 ton 4-sheave block w/web Wilson 150 ton hook, all the above mounted on franks 4 axle trailer s/n p206-010bd, hyd. & (4) manual leveling jacks, 295/75r22.5 tires, steel wheels.

13'w x 10'h x 19'l telescoping substructure 200,000# setback capacity, with rotary beam, rt 175 17-1/2" rotary table, v-door ramp, stairs, safety rails, 9'w x 12"h x 20'l mud boat.

Drillers house / water tank combo, 8'wx18'l crimped steel drillers house that swings up out of 8'11"wx5'3"hx30'l 230 bbl water tank, w /8'11" x 10'l crimped steel pump house, skidded

42"hx6'8"wx49'l single section catwalk w/ steel deck & contents

Generator / utility house / diesel tank, John Deere 12.5l 342kw ac generator, p/b john deere 12.5l diesel eng elec. start, radiator, skidded, international electric 250kw ac, generator p/b Detroit diesel 8v92 engine w/ elec. start, skidded, model 318vl air compressor p/b 2.5hp elec. motor w/ air volume tank, all mtd in 10'w x 42'l crimped steel house w/ parts room & 105 bbl. fuel tank