

NOV Rapid Rig Spec Sheet

Drawworks:

- NOV SSGD-250 A/C drive
- Baylor Model CM632UUT-129 VFD induction motor

Power:

- (2) Baylor 1750 KVA powered by MTU 16V2000 diesel engines
- 1000HP

Mast and Substructure:

- NOV 80' telescoping mast 500,000# SHL
- NOV 20' telescoping substructure 500,000# SHL (0 setback)

Mud Pumps:

- (2) NOV F-1000 powered by CM628TUT-119L VFD induction motor

A/C VFD UNIT:

- NOV N-10340-R1 A/C drive house

Traveling Equipment:

- NOV 250 ton split block

BOP Equipment:

- 5000 PSI choke manifold

Mud System:

- (2) pit mud system. 767 barrel capacity
- NOV mini cobra shakers
- Desilter, desander, centrifuge
- Agitators and centrifugal pumps
- Water tank 400 barrel capacity

Rig Houses:

- Driller shack
- Change house
- Parts house
- (4) Additional houses containing spare parts

Top Drive:

- NOV TDS-10 RR

Pipe Handling:

- NOV ST 80
- NOV Pipecat w/ wireless controls
- BJ BX 500 ton elevators
- NOV PS21 power slips

Other information:

- Cold start air compressor
- (2) Gardner Denver rig air compressors
- Hydraulic Drill line spooler
- Electric HPU
- Diesel powered HPU
- K6UL air tugger

Tubulars:

- 186 jts 5" 19.5 lb drill pipe G105 (range 3)
- 27 jts 8" drill collars
- 26 jts 5" heavy weight drill pipe

Manufactured 2008

Last drilled 2024

Lifting weight 500,000lbs

